

PB22, PB32 & PB50

Rugged Mobile Label Printers

A speedy choice for customers with demanding applications in warehouse, distribution, in-store retail and enterprise asset management, Honeywell's PB22, PB32 and PB50 rugged mobile label printers help organizations improve productivity and efficiency while lowering the total cost of ownership.

With ultra-fast print speeds and faster time-to-first-label than competing products, these printers deliver measurable improvements in worker productivity and accuracy. Unique design elements, such as the label gap and label take sensors, help maintain productivity while reducing waste.

PB series printers are a perfect complement to Honeywell mobile computers and software. Shared accessories across the family add flexibility and reduce spares inventory and associated costs. Genuine Honeywell media options, co-engineered specifically for the PB series, ensure consistently high print quality across a range of applications.

Characterized by a wide variety of options and a highly adaptable design, PB series printers feature drop-in media loading, adjustable media holders, and the flexibility to printer either receipts or labels—so workers can easily change tasks without changing equipment. A choice of secure wired and wireless interfaces (WLAN, Bluetooth®, Serial, USB) fits easily into varied network infrastructures.



Rugged PB22, PB32 and PB50 printers are ready to ramp up productivity in the most demanding in-store retail, DC or warehouse environments.

The rugged design of the PB series means dependable performance—day after day. Built to thrive in the same environments as Honeywell's rugged computers and scanners, these printers have a 1.5 m (5 ft) drop spec, IP54 seal rating, and forklift-strength shock and vibration specifications.

FEATURES & BENEFITS



Built to survive real-world mobility demands, with a 1.5 m (5 ft) drop spec and IP54 seal rating.



Sophisticated sensors and intuitive LCD display minimize wasted time troubleshooting.



Seamless integration with Honeywell mobile computers and other mobile devices.



Secure wire or wireless communication options, including Bluetooth®, WLAN, USB, and serial.



Co-engineered with Genuine Honeywell Media Supplies for guaranteed label quality.

PB22, PB32 & PB50 Technical Specifications

PHYSICAL CHARACTERISTICS

PB22:

Width: 101 mm (4 in)
Height: 176 mm (6.9 in)
Depth: 71 mm (2.8 in)
Weight (with battery): 678 g (23.9 oz)

PB32:

Width: 127 mm (5 in)
Height: 182 mm (7.2 in)
Depth: 81 mm (3.2 in)
Weight (with battery): 828 g (29.2 oz)

PB50:

Width: 160 mm (6.3 in)
Height: 174.5 mm (6.9 in)
Depth: 78.8 mm (3.1 in)
Weight (with battery): 1189 g (42.0 oz)

ENVIRONMENT

Operating temperature: -15°C to 50°C
(5°F to 122°F)

Storage temperature: -30°C to 70°C
(-22°F to 158°F)

Humidity: 10 to 90% (non-condensing)

Sealing: IP54 (excludes paper path)

Drop spec (PB22/32) 2 m (6.5 ft) multiple drops to concrete with optional protective case

Drop spec (PB50): 1.5 m (5 ft.) drops to concrete; 26 times including all corners and sides

POWER

PB22/32: 7.4 V Li-Ion, 2.3 Ah, rechargeable battery (typical)

PB50: 14.8 V Li-Ion, 2.2 Ah, rechargeable battery

MEMORY

RAM: 16 MB

Flash: 64 MB

STANDARD COMMUNICATIONS

RS-232 Serial

USB v.2.0

OPTIONAL COMMUNICATIONS¹

Bluetooth® (v2.0, Class 1)

802.11b/g (excludes ETSI models)

802.11b/g/n Dual-Band (2.4GHz) & 802.11a (5GHz) (ETSI models only)

WIRELESS SECURITY

Authentication & Encryption Options: WEP (64 & 128 bit); LEAP; WPA-PSK (TKIP / RC4); WPA2/802.11i-PSK (CCMP / AES);EAP-TLS, -TTLS, -PEAP, -FAST

PRINT SPEED AND RESOLUTION

4 ips (101.6 mm/sec)
203 dpi (8 dots/mm)

PRINT TECHNOLOGY

Printhead: Direct thermal

MEDIA

Type: Labels or receipt media

Honeywell Genuine Media Supplies:

Labels and Tags: Duratherm II, Duratherm III, Duratherm NIR, Duratherm III IR, Duratherm III Synthetic, Duratherm III Linerless, Duratherm II 5-mil Tag
Receipts: Duratherm Receipt II, Duratherm Receipt III

Media Width Ranges:

PB22: 25.4 mm to 55.88 mm (1 to 2.2 in)

PB32: 30.48 mm to 83.82 mm (1.2 to 3.3 in)

PB50: 49 mm to 111.5 mm (2 to 4.39 in)

Core ID: 19 mm (0.75 in) standard, 10.16 mm (0.4 in) supported

Max OD:

PB22: 57.2 mm (2.25 in)

PB32: 67.3 mm (2.65 in)

PB50: 67.3 mm (2.65 in)

CHARACTER SETS

Standard: English and Latin

Optional: Western European, ASCII, CodePage 850, Central European, Cyrillic, Latin, Greek, Turkish, Hebrew, Arabic, Baltic, Baltic RIM, Vietnamese, Thai, Simplified Chinese, Traditional Chinese, Korean, UTF-8

GRAPHICS

Supports user-defined fonts, graphics, formats and layouts, including custom logos

BARCODE SYMBOLOGIES

All major 1D and 2D symbologies are supported.

USER INTERFACE

LCD and 4 buttons: standby, paper feed, setup, info four audio status indicators: error alert, hardware change alert, button press alert and startup alert.

ACCESSORIES

Hand strap, shoulder strap, belt clip, protective case, cart mount, vehicle mount, battery pack, four-bay battery charger, A/C adapter, A/C power cord, truck power cable adapter, truck power cable, forklift power cable, serial cable

SAFETY APPROVALS

North America: UL and cUL Listed, UL 60950-1

Europe: D Mark, EN 60950-1; CE marked

Mexico: NYCE Certified, NOM 19

Other Countries: IEC 60950-1

EMC APPROVALS

USA FCC Title 47, Part 15, Subpart B, Class B; Europe EMC Directive (EN55022 Class B + EN55024); CISPR22

SOFTWARE

Programming Languages: IPL, Fingerprint, ZSim (ZPLII Simulation), ESC-P, DSim (DPL), CSim (CPCL)

Applications: PrintSet Configuration Utility; Bartender Ultralite Labeling Software; SmartSystems™ Foundation Console/Server Software; Bootloader Utility; Drivers & Support for Linux/BSD (1.1,1.2), SAP, & Wavelink® Avalanche; InterDriver Printer Drivers for Microsoft® Windows® operating system

WARRANTY

One year; additional Honeywell Repair Services packages available

¹ Not all communication options are available in all regions. Contact your Honeywell representative for more information.

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance.

For a complete listing of all supported barcode symbologies, please visit www.honeywellaidc.com/symbologies.

Honeywell Sensing and Productivity Solutions

9680 Old Bailes Road

Fort Mill, SC 29707

800-582-4263

www.honeywell.com

PB22-PB32-PB50-DS Rev 12/15
© 2015 Honeywell International Inc.

Honeywell