



MD15V

CE FC RoHS

Key feature ▶

- ※ Durable 15" POS screen with ultra stable base
- ※ 5-wire resistive touch layer or non-touch version
- ※ Optional MSR and second client display
- ※ Low power consumption



Model Name	MD15V
TFT LCD	15" LCD panel (4:3) / LED backlight
Supply voltage	DC 12V
Display surface	Anti-glare
Resolution	1024x768
Contrast ratio	800:1
Brightness	420cd/m ²
Viewing angle	H: 160° , V: 160°
Color	Deep gray or customized
Response time	16ms
Video interface	Analog (VGA)
Touch interface (option)	USB or RS232
Touch panel type(option)	5 Wire Resistive Touch screen
Touch panel Lifetime(option)	35Million times(finger touch)
Power consumption	<24W
Maximum dimensions in mm(W x D x H)	370x200x350
Maximum dimensions in inches (WxDxH)	14.6x7.9x13.8
Package dimension	420*400*205mm
Gross weight	6.5kg
Backlight MTBF	30000hrs Min
Temperature, Operating	0 – 55°C
Humidity, Operating	10% – 85% non-condensing
Temperature, Storage	-20 – 60°C
Humidity, Storage	10% – 85% non-condensing
Standards compliance	FCC class-B,CE class-B ,RoHS

All product specifications are subject to change without notice.